



MODEL NO.	NUMBER OF BALL	MAIN DIMENSIONS										ECCEN-TRICITY	BASIC LOAD RATING				
		INSCRIBED CIRCLE		OUTER DIAMETER		LENGTH		OUT LOCKING GROOVE			W		C(kgf)	Co(kgf)			
		dr	TOLERANCE	D	TOLERANCE	L	TOLERANCE	B	TOLERANCE	D1							
LM04UU	4	4	0	8	0	12	0					0.008	9	13			
LM05UU	4	5	-0.008	10	-0.009	15	-0.12	10.2			9.6	1.1	17	21			
LM6UU	4	6	0 -0.009	12	0 -0.011	17	0 -0.20	13.5	0 -0.20		11.5	1.1	0.012	21	27		
LM8SUU	4	8		15		19		11.5		14.3	1.1	18		23			
LM8UU	4	8		15		24		17.5		14.3	1.1	27		41			
LM10UU	4	10		19		29		22		18	1.3	38		56			
LM12UU	4	12		21		30		23		20	1.3	42		61			
LM13UU	4	13		23	-0.013	32		23		22	1.3		52	79			
LM16UU	5	16		28		37		26.5		27	1.6		79	120			
LM20UU	5	20		32		42		30.5		30.5	1.6		88	140			
LM25UU	6	25	0 -0.010	40	0 -0.016	59	0 -0.30	41	0 -0.30		38	1.85	0.015	100	160		
LM30UU	6	30		45		64				44.5		43		1.85		160	280
LM35UU	6	35		52		70				49.5		49		2.1		170	320
LM40UU	6	40	0 -0.012	60	0 -0.019	80				60.5		57		2.1	0.02	220	410
LM50UU	6	50		80		100				74		76.5		2.6			390
LM60UU	6	60	0 -0.015	90	0 -0.022	110		85		86.5	3.15	0.025	480	1020			